HP/kW | MF415 A6/34 | Narrow

Simple and powerful specialist narrow tractors from Massey Ferguson available with 2 or 4wd and folding ROPS - compact in size, big in performance



VISION INNOVATION LEADERSHIP QUALITY RELIABILITY SUPPORT PRIDE COMMITMENT

Performance		MF 415
Max. Power	hp (kW) (ISO14396)	46 (34)
Max. Torque	Nm @1350 rpm	167
Rated Speed		2250
Engine	'	
Engine Type	Tier 0	A3-2.5
No. of Cylinders		3
Capacity	cc	2500
Aspiration		Natural
Transmission		
8 x 2 Centre Shift		1
Power Take Off		
Live Drive	540 rev/min	
IPTO	540 rev/min	m
Steering		
Type		Hydrostatic
Hydraulics		3 1 1 1 1 1
3 Point Linkage Control		Mechanical
Lift Capacity	kg	2,100
Oil Flow	litres/min	17
System Pressure	bar	210
Selector Valve		Std
Spool Valves		1 Std
Brakes		
Туре		Oil Immersed
Standard Wheels and Tyres		
Front 2wd / 4wd		6.00-16 / 8.00-18
Rear 2wd / 4wd		14.9-24
Weights and Dimensions* 2wd /4wd	'	
Shipping Weight	kg	2,230 / 2,400
Wheelbase	mm	2,000
Overall Length	mm	3,700
Height (With ROPS)	mm	2,260
Minimum Height (ROPS Folded)	mm	1,470
Track Width min - Front	mm	1,077 / 1,180
Track Width min - Rear	mm	1,025
Minimum Outside Rear Width	mm	1,310
Turning Circle with Brakes	mm	3,100 / 3,180
Turning Circle less Brakes	mm	3,440 / 3,510
Capacities		
Fuel Tank	litres	57
Engine Oil	litres	5.5

litres





Transmission Oil

For even greater productivity a range of optional equipment is available including front weights, rear-wheel weights, two-post folding ROPS frame. For full details please consult your local Massey Ferguson dealer.

42

- = Standard
- m = Optional
 * = With Standard Wheels
 and Tyres